



# — PRODUCT DATA SHEET

## P7 Core



# P7 Core

## PRODUCT DESCRIPTION

The P7 is one of our most iconic flashlights still to this day, and we've decided to give it some design upgrades. The P7 Core as successor of the P7 still has one of our most innovative light technologies, the patented<sup>3</sup> Advanced Focus System, which allows a continuous transition from a broad flood beam to a sharply focused long-distance beam. In addition, the P7 Core features Rapid Focus technology for single handed operation and continues to use four AAA alkaline batteries.

- Advanced Focus System for efficient, precise flood and spot lighting
- Outstanding Ledlenser light quality brightness, beam range and run time are ideally matched to the energy source
- Fast change of light cone with Rapid Focus
- Battery powered with four AAA alkaline batteries
- Easy operation by Endcap Switch

### TECHNICAL DATA

|                              |                      |
|------------------------------|----------------------|
| Length defocused [mm]        | 130                  |
| Length focused [mm]          | 140                  |
| Head diameter [mm]           | 37                   |
| Tube diameter [mm]           | 30                   |
| Weight incl. batteries [g]   | 175                  |
| Weight without batteries [g] | 130                  |
| Focus function               | Yes                  |
| Head material                | Aluminum alloy       |
| Tube material                | Aluminum alloy       |
| Optic                        | Plastic lense (PMMA) |
| Cartridge                    | Yes                  |

### POWER SUPPLY

|                   |               |
|-------------------|---------------|
| Power source type | Battery       |
| Battery quantity  | 4             |
| Battery type      | Alkaline      |
| Rechargeable      | No            |
| Energy modes      | Energy Saving |
| Usable batteries  | AAA NiMH 1.2V |

### FURTHER SPECIFICATIONS

|                                |            |
|--------------------------------|------------|
| IP class                       | IP54       |
| Drop test (drop height) [m]    | 1          |
| Working temperature range [°C] | -20 to +40 |

### LIGHT FUNCTIONS

Low Power, Mid Power, Power

### LIGHT SOURCE

|                             |              |
|-----------------------------|--------------|
| Amount LEDs                 | 1            |
| LED type                    | Xtreme LED   |
| Color                       | White        |
| Color temperature [K]       | 6000 to 7500 |
| Color rendering index (CRI) | 70           |

### LIGHT VALUES

| ANSI – Energy Saving           | Boost | Power | Mid Power | Low Power |
|--------------------------------|-------|-------|-----------|-----------|
| Light output <sup>1</sup> [lm] |       | 450   | 250       | 40        |
| Beam distance <sup>1</sup> [m] |       | 300   | 220       | 100       |
| Run time <sup>1</sup> [h]      |       | 1     | 2         | 25        |

### SWITCH

End Cap Switch

### TECHNOLOGIES

Advanced Focus System<sup>3</sup>, Rapid Focus

# P7 Core

## PACKAGING AND LOGISTICS



### PACKAGING INFORMATION

|                       |                                   |
|-----------------------|-----------------------------------|
| Type of packaging     | Box                               |
| Scope of delivery     | 1 set of batteries,<br>Hand strap |
| Item No.              | 502180                            |
| Customs tariff number | 85131000000                       |
| Color                 | black                             |
| MSRP price (€)        | 74.90                             |

### SINGLE PACKAGE

|                           |                |
|---------------------------|----------------|
| Dimensions W x H x D [cm] | 7.2 x 21 x 8.5 |
| Gross weight [g]          | 313.6          |
| GTIN-13                   | 4058205020480  |

### EXPORT CARTON

|                           |                |
|---------------------------|----------------|
| Unit                      | 24             |
| Dimensions W x D x H [cm] | 45.5 x 29 x 34 |
| Gross weight [kg]         | 8.28           |
| GTIN-13                   | 4058205020503  |

# P7 Core

## ACCESORIES

| PRODUCT CATEGORY           | ITEM NUMBER | PRODUCT NAME                         | MSRP    |
|----------------------------|-------------|--------------------------------------|---------|
| Color filter / Signal caps | 0040        | Signal Cone 37mm                     | 6.90 €  |
| Fastenings / Brackets      | 0317        | Intelligent Clip Type C              | 8.90 €  |
| Pouches / Holster          | 0333        | Pouch Type A                         | 9.90 €  |
| Fastenings / Brackets      | 0362        | Universal Mounting System            | 14.90 € |
| Fastenings / Brackets      | 501033      | Magnetic Mount                       | 39.90 € |
| Pouches / Holster          | 0323        | Tactical Professional Holster Type B | 34.90 € |

# P7 Core

## PRODUCT SERIES

The robust and reliable Ledlenser P-series flashlights offer great performance in a stylish design. Externally reduced to the essentials, they are packed with many useful technologies, such as the patented<sup>3</sup> Advanced Focus System or the advanced Smart Light Technology for individual programmability. Many products are protected against dust and water thanks to the innovative Flex Sealing Technology. The new P-series is also the first Ledlenser range of flashlights designed for all user fields. The products of the Core, Work, and Signature range have different designs and are therefore tailor-made for different target groups.

Our Core collection is at the heart of our new P-series lights. Perfect for everyday use in home and garden, for crafts and industry, but also for many recreational applications. The lamps of the Core range offer innovative technologies and functions as well as great performance for the price.

---

## FOOTNOTES

The information pertaining to scope of delivery, appearance, performance, dimensions and weight corresponds to the information available at the time of publication. In the interest of product development, we reserve the right to change scope of delivery, appearance, design and color without prior notice. Product images may vary from the actual products and may show optional accessories which can be purchased separately. Errors and omissions excepted.

1) Measurement values according to ANSI FL1 in the respective setting. If no setting is explicitly indicated, the values refer to luminous flux (lumens/lm) and lighting range (meters/m) on the highest setting, and to battery duration (hours/h) on the lowest setting. A boost function (if available) can be used several times, but only for short periods of time. If the light is equipped with (a) colored LED(s), the measurement values are given for the white light or the white LED. If the light has different energy modes, the measurement is made based on the "energy saving mode".

3) EP Patent 1880139, US Patent 7,461,960